



# “Rapid” Hose Clamp

## with quick-release closure

### Application

- Fuel line systems
- Lines carrying air
- Cooling water/Heating
- General retainer/Fastener
- Oil, low-pressure hydraulics

### Advantages

**Quick-release closure**  
(from clamping range 25 - 40 mm)

Quick and easy premounting via “ratchet effect”

**Strap perforation cover/Turned-up\* edges**

Prevents injury and hose damage

**Long hex. head**

Secure turning while mounting, even when out of view.

### Technical Data

Material of strap/body	1.4310 stainless steel A2
Material of screw	steel with zinc/nickel plating
Screw type	slotted/hex. head
Strap width	14.3 mm
Size	8 mm

### Delivery Overview

Clamping range in mm	Art. No.	P. Qty.
12 - 22	<b>0547 312 022</b>	25
16 - 27	<b>0547 316 027</b>	
20 - 32	<b>0547 320 032</b>	
25 - 40	<b>0547 325 040</b>	
35 - 50	<b>0547 335 050</b>	
40 - 60	<b>0547 340 060</b>	10

Clamping range in mm	Art. No.	P. Qty.
50 - 70	<b>0547 350 070</b>	10
60 - 80	<b>0547 360 080</b>	
70 - 90	<b>0547 370 090</b>	
80 - 100	<b>0547 380 100</b>	
90 - 110	<b>0547 390 110</b>	
100 - 120	<b>0547 300 120</b>	

Clamping range in mm	Art. No.	P. Qty.
110 - 130	<b>0547 310 130</b>	10
130 - 150	<b>0547 330 150</b>	
150 - 170	<b>0547 350 170</b>	
160 - 180	<b>0547 360 180</b>	
190 - 210	<b>0547 390 210</b>	5

### Method of functioning of the quick-release closure



Push clamp strap into buckle; buckle disengages



Lift disengaged buckle screw and pull strap out of the buckle



Wrap opened clamp around the hose



Pretension clamp via ratchet effect



Tighten clamp with tool

### Additional Products



## Screwdriver Size 8

with flexible shaft

**Art. No. 0613 286 08**

P. Qty. 1