

Abrasive materials range: Dry sandpaper, wood

Application

- High-grade abrasive paper for hand sanding.
- Especially for wood; the fine grains are also suitable for softer varnishes such as water varnish.
- High sanding performance and durability due to synthetic resin bond.
















Features of the Abrasive Papers KPE & KPC

+ = KPE Quality (corundum paper E)

- Grain: 40–100 discs and sheets
40–150 rolls
- Paper weight/m² = 200–250 gr. = E paper
- Synthetic resin bond
- Aluminium oxide (special fused alumina)

x = KPC Quality (corundum paper C)

- Grain: 120–280 discs, sheets, rolls
- Paper weight/m² = 105–115 gr. = C paper
- Synthetic resin bond
- Aluminium oxide (special fused alumina)

Dimension Design/Hole	Adhesion system		Grit sizes									
	Hook and loop	Without	40	60	80	100	120	150	180	220		
 8	0583 531		+	+	+	+	x	x	x	x		
 8	0583 541		+	+	+	+	x	x	x	x		
 8 outside	0583 542		+	+	+	+	x	x	x	x		
 150	0583 550		+	+	+	+	x	x	x	x		
 6 inside	0583 552		+	+	+	+	x	x	x	x		
 8 outside	0583 553		+	+	+	+	x	x	x	x		
 70 120	0583 570				+	+	+	+	+			
 Festo 8 81 133	0583 575		+	+	+	+	x	x	x	x		
 SSE-80 8 81 133	0583 576		+	+	+	+	x	x	x	x		
 8 93 178	0583 580		+	+	+	+	x	x	x	x		
 10 115 228	0583 585		+	+	+	+	x	x	x	x		
 115 280	0583 590		+	+	+	+	x	x	x	x		
 105 115	0583 595		+	+	+	+	x	x	x	x		
 6 90	0583 598		+	+	+	+	x	x	x	x		
 115mm x 50m	0583 115 0583 215		+	+	+	+	+	+	x	x		