



Useit® Superpad Wood

The perforated sanding disc for treated and untreated hardwood and softwood, fillers, plastics, gypsum plasterboards, paints, hard and soft paint systems and mineral materials (artificial stone).

Sanding disc perforated over entire surface.

Your advantages:

- The sanding dust is vacuumed away completely from the entire surface.
 - No clogging, high sanding capacity, long service life, even sanding pattern.
 - Dust and shade-free operation.
- Shorter sanding time and effective working with a sanding capacity up to four times that of ordinary perforated sanding materials.
 - Saves time and money.
- In contrast to ordinary perforated sanding materials, the hole pattern of the Würth Useit® Superpad Wood has been optimised for the material and the resulting dust.
 - No clogging of the sanding disc.
- The Würth Superpad Wood is universally suitable for use with any sanding plate (regardless of holes) - whether with or without dust extraction.

Base material: D paper (grain P80 – P240)
 Colour: Yellow
 Grain: Aluminium oxide
 Bond: Synthetic resin bond
 Base material: C paper, extra strong (grain P280 – P600)
 Colour: Gold
 Grain: Specially hardened corundum (aluminium oxide)
 Bond: Synthetic resin bond (stearate-coated)
 Adhesion system: Velcro



Dimension/ Type	Art. No.	Grain sizes														P. Qty.	
		40	60	80	100	120	150	180	220	240	320	400	500	600			
	125 mm dia. 0581 202	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	25
	150 mm dia. 0581 203	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	
	200 mm dia. 0581 204	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	
	225 mm dia. 0581 205	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	
	70x120 mm 0581 210	+	+	+	+	+	+	+	+	+	+	+	+	+	+		
	81x133 mm 0581 212	+	+	+	+	+	+	+	+	+	+	+	+	+	+		
	93x178 mm 0581 213	+	+	+	+	+	+	+	+	+	+	+	+	+	+		
	115x115 mm 0581 214	+	+	+	+	+	+	+	+	+	+	+	+	+	+		
	115x228 mm 0581 215	+	+	+	+	+	+	+	+	+	+	+	+	+	+		
	115x280 mm 0581 216	+	+	+	+	+	+	+	+	+	+	+	+	+	+		
	93x93x93 mm 0581 220	+	+	+	+	+	+	+	+	+	+	+	+	+	+		
	100x147 mm 0581 221	+	+	+	+	+	+	+	+	+	+	+	+	+	+		
	120x120x120 mm 0581 222	+	+	+	+	+	+	+	+	+	+	+	+	+	+		
	115 mm x 18 m 0581 230	+	+	+	+	+	+	+	+	+	+	+	+	+	+	1	

Permanent dust extraction over the entire sanding surface

- Full-surface extraction
- Cooler sanding
- No clogging
- Higher surface sanding capacity

Conventional sanding system

Note:

The disc diameter of 225 mm is especially for dry construction for sanding gypsum plasterboards to which filler has been applied (suitable for the "Giraffe" long-neck sanding machine).

