

## COMPRESSED AIR ANGLED IMPACT WRENCH DWSS 1/2 INCH



<b>Art. No.</b>	<b>5714 300 0</b>
<b>P. Qty.</b>	1
<b>Bit size</b>	1/2 inch
<b>Max. working torque</b>	190 Nm
<b>Max. releasing torque</b>	244 Nm
<b>Sound-pressure level</b>	97 dB
<b>Vibration</b>	43.5 m/s <sup>2</sup>
<b>Weight of machine</b>	1.8 kg

Related products for	Designation	Art. No.
5714 300 0	Male thread plug-in nipple Series 2000	<b>0699 100 614</b>
	Small mist oiler	<b>0699 070 314</b>
	Special oil	<b>0893 050 5</b>

### Application area

Assembly and disassembly of crankshaft, exhaust, installation and removal of turbocharger, generator etc.

### Notice

When the impact wrench is used regularly, a little oil should be added daily through the compressed air, and approximately 2 strokes of gear grease should be added monthly via the grease nipple.

**Powerful compressed air angled impact wrench with low head height for working in constricted spaces.**

**High-quality hammer impact mechanism and cylinder with 7-disc motor**

For reliable, high performance values and a long service life.

**2-stage power setting with convenient right/left rotation control**

Always optimal, user-friendly adjustment to the application concerned.

**Ergonomically formed soft grip handle with sensitive trigger**

No cooling of the handle when working, good handling and optimal control.

**Very low head height of just 50 mm**

Ideal for use where access is restricted (e.g. engine compartment)

**3 Years Warranty**

on issues of material and production