INDUSTRIAL VACUUM CLEANER FOR WET AND DRY MATERIALS ISS 55-S AUTOMATIC

Art. No.	0701 156 1
P. Qty.	1
Max. power	1,380 W
Min./max. nominal voltage	220 / 240 V/AC
Min./max. frequency	50/60 Hz
Container contents	54 l
Underpressure	230 mbar
Air stream	61 l/s
Nominal width	40 mm

Delivery scope for Art. No.	Designation	Art. No.	Quantity
0701 156 1	Fleece Wet & Dry Filter Bag	0702 400 072	1
	Clip-on reduction piece	0702 400 108	1
	Flat folding filter, coated	0702 400 191	1
	Universal connection piece for dust extraction	0702 400 247	1
	Metal tube, insertable	0702 400 276	1
	Wet/dry floor attachment, insertable	0702 400 285	1
	Clip-on suction hose	0702 400 321	1
	Clip-on elbow	0702 400 905	1

Building and metal vacuum cleaner (with supplemental accessories). For use with a core drill and for general cleaning work.

Automatic filter cleaning system

- Constant high vacuum power, no manual actuation via a pushbutton is necessary. The flat folding filter is cleaned automatically via an air blast approximately every 15 seconds (pulsing noise).
- Long operating time without filter change, low maintenance costs

Stepless speed control

Individual adjustment of the vacuum power.

Flat folding filter does not extend into the container.

Optimum utilization of the canister size.

Anti-static prepared

With separate anti-static accessories (electrically conductive suction hose, electrically conductive connection sleeve). Can conduct an electrostatic charge originating e.g. during the grinding of plastic away from the user.

3-year warranty

On manufacturing and material defects

Application

Ideal for vacuuming oils, lubricants and chips (e.g. lathe).

Note

Available in the ORSYfleet fleet management system

- Dry vacuuming only with dust bag and folding filter. Do not vacuum without a filter system, or else the vacuum motor can be damaged.
- Wet vacuuming with PES flat folding filter.

STEP - 8/8/2014 - 17174 - ©