

CRAFTSMAN'S VACUUM CLEANER

Technical information on HWS 15-L



- 1 Steering castor
- 2 Filter cleaning button
- 3 Button for locking vacuum tank in chassis
- 4 Button for automatic switch-on/switch-off function of socket outlet
- 5 Clamping cables
- 6 Socket Outlet
- 7 Main switch
- 8 Adapter plate
- 9 Carrying handle of adapter plate
- 10 Adapter plate lock
- 11 Elbow
- 12 Housing module for filter cleaning
- 13 Vacuum hose
- 14 Fold-in push handle
- 15 Large wheels

Technical Data

Voltage	V/Hz	220 - 240/50 - 60
Protection class		Ⓢ/I
Max. power	W	1,380
Nominal power	W	1,200
Tank capacity	lt	14
Liquid filling capacity	lt	4
Power connection value for tools	W	100 - 2,200
Max. air flow rate	m ³ /h	100
Max. vacuum	mbar	205
Max. ambient temperature	°C	+ 40
Vacuum hose connection (nominal dia.)	mm	35
Cable length	m	7.5
Sound pressure level	dB (A)	68
Dimensions (L x W x H)	mm	595 x 465 x 460
Weight	kg	16.5

Accessories

Fig.	Designation	Art. No.	P. Qty.
12	Wet-and-dry fleece filter bag	0702 400 070	5
13	PES flat folding filter	0702 400 195	1
14	Adapter plate for Systainer case system	0702 400 002	1

