

MAGAZINE SCREW ATTACHMENT



High-speed construction screwdriver must be ordered separately.

Delivery scope		
Designation	Art. No.	P. Qty.
Magazine screw attachment for S 50-TB	-	1
1/4"-PH2 bit, length 176.5 mm	0614 100 212	2



Overview of available belted screws			
Dimensions in mm	Art. No. Two speeds	Art. No. Coarse thread	Art. No. Cement panel screws
3.9 x 25	0179 339 25	0179 839 25	-
3.9 x 35	0179 339 35	0179 839 35	-
3.9 x 45	0179 339 45	0179 839 45	-
4.0 x 25	-	-	-
4.0 x 30	-	-	0179 64 30
4.0 x 35	-	-	-
4.0 x 40	-	-	-
4.0 x 45	-	-	0179 64 45

Additional dimensions on request.

Essential for all dry construction workers and wherever serial screw connections save time. Especially well-suited for dry construction screws.

Separate in box. With matching adapter for S 50-TB, TBS 18-A and two PH2 bit.

S 50 TB-M

For S 50-TB and TBS 18-A

Art. No. 0702 050 100

For belted screws.

Enormous time savings for serial screw connections. As a result, the higher purchase costs quickly pay off.

For screws from 3.5 x 25 mm to 4.2 x 55 mm.

High working flexibility.

Extremely handy and light.

Even working for longer periods can be carried out without a high exertion of force.

3-year warranty.

On manufacturing and material defects.

Available in the fleet management system ORSY®fleet.

Accessories		
Designation	Art. No.	P. Qty.
1/4"-PH2 bit, length 176.5 mm	0614 100 212	3
1/4"-AW®20 bit, length 176.5 mm	0614 100 420	3
S 50-TB Dry Construction Screwdriver	0702 050 0	1
Matching Empty Case	0955 250 400	1