

## BLOW-OUT GUN

- Cast aluminum
- With standard short nozzle
- Brass coupling connector with 1/4" connection

Weight in g	Nozzle bore dia. in mm	Art. No.	P. qty.
250	1.5	<b>0714 92 13</b>	1

### Extension Nozzles

- Brass, nickel-plated
- Angled

Length in mm	Weight in g	Thread dia. in mm	Nozzle bore Dia. in mm	Art. No.	P. Qty.
100	37	M 12 x 1.25	3	<b>0714 92 14</b>	1
150	47			<b>0714 92 15</b>	
250	54			<b>0714 92 16</b>	

### Safety Noise-Control Nozzle

- Die-cast zinc, chrome-plated. Up to 2.5 times more blowing power compared with a classic single-hole blower nozzle
- Reduces the noise level to up to 74 db (A).  
The noise level with conventional nozzles can be approx. 90 db (A). Just 8 db (A) lower sounds half as loud to the human ear!
- Conical shape provides protection against direct contact with skin.

Weight in g	Max. pressure bar	Thread dia. in mm	Art. No.	P. Qty.
20	16	M12 x 1.25	<b>0714 92 17</b>	1

## COMPRESSED AIR GUN

- Steplessly adjustable
- Insulated ergonomic handle
- Lightweight robust construction

Tube shape	Length in mm	Art. No.	P. Qty.
Angled	90	<b>0714 921 1</b>	1
Straight	320	<b>0714 921 3</b>	
Straight	490	<b>0714 921 4</b>	

### Technical data:

Max. working pressure	16 bar
Air consumption at 6 bar inlet pressure	500 l/min
Temperature range	-20 °C to +80 °C




### Attachment possibility:

	Art. No.
Threaded grommet, 1/4" - 6 mm	<b>0699 461 4</b>
Threaded grommet, 1/4" - 9 mm	<b>0699 491 4</b>
Plug-in nipple, 1/4" male thread	<b>0699 100 614</b>

### Note:

Bypass function: If a surface is too close, the air will escape to the side. The pressure on the objects is thus reduced to max. 1.6 bar.



Attachment piece	A in mm	C in mm	Wt. in g	Art. No.	P. Qty.
Plastic guard with bypass 	36.5	100	32	<b>0714 92 23</b>	1
Rubber mouthpiece 	46.5	14	9	<b>0714 92 24</b>	
Effect enhancer with bypass 	54.0	14	11	<b>0714 92 25</b>	