

Hydraulic Trolley Jacks

- Sturdy frame construction.
- Convex rollers and swivelling wheels with ball-bearings ensure a high degree of manoevrability.
- The safety valve means that, in case of overloading, the lifting rod will go into no-load operation.
For safety, however, the lifting height remains constant.
- Additional foot pedal for quick lifting.
- Secure and precise control when lifting and lowering thanks to easy-to-operate lifting rod.
- Lifting rod with ergonomic, rubber-coated handle.



RHC-2 trolley jack

Art. No. 0715 54 100

Pack Qty.: 1

- Load capacity 2,000 kg.
- Extremely low saddle height (80 mm) for low-lying mounting points.
- Nylon wheels for non-damaging, smooth travel.
- Foot pedal for activating the quick-lift function.

Accessories:

Saddle cushion made from oil-resistant rubber

Art. No. 0715 54 170

Axle crosspiece, 1,200 kg load capacity

Art. No. 0715 54 14



Trolley jack RHC-2H

Art. No. 0715 54 140

Pack Qty.: 1

- Load capacity 2,000 kg.
- Extremely large lifting height (735 mm) for creating maximum free space under the vehicle.
- Nylon wheels for non-damaging, smooth travel.
- Foot pedal for activating the quick-lift function.

Accessories:

Saddle cushion made from oil-resistant rubber

Art. No. 0715 54 170

Axle crosspiece, 1,200 kg load capacity

Art. No. 0715 54 14



RH-4 trolley jack

Art. No. 0715 54 150

Pack Qty.: 1

- Load capacity 4,000 kg.
- Foot pedal for activating the quick-lift function.
- Supplied without pneumatic wheels.

Accessories:

Pneumatic wheels for high steerability

Art. No. 0715 54 15