

Simplex Rubber-Headed Mallets

- Head inserts and shaft can be quickly replaced.
- Inserts and shaft are firmly attached and cannot be displaced.
- The rubber-headed hammer is available as individual parts.
- Changeable head inserts give you two rubber-headed hammers in one.
- Complete with inserts: rubber composite - black, and plastic - red.



Ø mm	Hammer length mm	head length mm	Shaft length mm	Weight g	Art. No.	
40	330	110	278	655	0715 72 10	1
50	365	135	312	1130	0715 72 20	
60	400	150	335	1580	0715 72 27	
80	500	170	395	3080	0715 72 28	
80	800	170	700	3290	0715 72 29	

Head inserts

Ø mm	Design	Area of application	Properties	Art. No.	
40	Plastic red	numerous applications	grease- and oil-resistant	0715 72 13	2
50				0715 72 23	
40	Rubber composite black	numerous applications	Shore hardness approx. 95 A	0715 72 14	
50				0715 72 24	
60				0715 72 275	
80				0715 72 285	
60	Superplastic white	especially suitable for edge blows	acid- and alkali-resistant	0715 72 274	
80				0715 72 284	
40	Nylon white	for powerful precision blows	grease- and oil-resistant	0715 72 15	
50				0715 72 25	
40	Soft metal silver	equivalent to lead hammer	heat-resistant	0715 72 16	
50				0715 72 26	

Malleable cast iron casing

Ø mm	Art. No.	
40	0715 72 11	1
50	0715 72 21	

Hammer shaft

Ø mm	Art. No.	
40	0715 72 12	1
50	0715 72 22	
60	0715 72 271	
80	0715 72 281	
80	0715 72 291	

Non-Rebounding Hammer

- Nylon head inserts.
- Casing filled with: steel shot.
- As the hammer strikes, the steel shot acts as though delivering additional blows.
- No power loss due to rebounding.

Head inserts for non-rebounding hammer

Ø mm	Art. No.	
30	0715 72 53	1 = 1 Pair
40	0715 72 55	
50	0715 72 57	
60	0715 72 59	



Ø mm	Head length mm	Total length mm	Weight g	Art. No.	
30	110	350	400	0715 72 52	1
40	120	375	700	0715 72 54	
50	130	385	1000	0715 72 56	
60	165	420	1650	0715 72 58	