

BLIND RIVET, ROUND PAN HEAD DIN EN ISO 15977

Nominal diameter (d ₁)	Length (l ₁)	Head diameter (d _k)	Screw-head height (k ₁)	Drill hole diameter	Min./max. clamping range	Mandrel diameter (d _m)	Shear-fracture load	Tensile fracture load	Nominal diameter x length (Ø d x l)	Art. No.	P. Qty.
4.8 mm	28.0 mm	9.5 mm	1.1 mm	4.9 mm	20.0-23.0 mm	2.70 mm	1690 N	2230 N	4.8 x 28.0 mm	5141 548 28	250
4.8 mm	30.0 mm	9.5 mm	1.1 mm	4.9 mm	23.0-25.0 mm	2.70 mm	1690 N	2230 N	4.8 x 30.0 mm	5141 548 30	250
4.8 mm	35.0 mm	9.5 mm	1.1 mm	4.9 mm	25.0-30.0 mm	2.70 mm	1690 N	2230 N	4.8 x 35.0 mm	5141 548 35	250
4.8 mm	40.0 mm	9.5 mm	1.1 mm	4.9 mm	30.0-35.0 mm	2.70 mm	1690 N	2230 N	4.8 x 40.0 mm	5141 548 40	250
5.0 mm	6.0 mm	9.5 mm	1.1 mm	5.1 mm	1.5-2.5 mm	2.70 mm	2000 N	2500 N	5.0 x 6.0 mm	5141 550 6	500
5.0 mm	8.0 mm	9.5 mm	1.1 mm	5.1 mm	2.5-4.0 mm	2.70 mm	2000 N	2500 N	5.0 x 8.0 mm	5141 550 8	500
5.0 mm	10 mm	9.5 mm	1.1 mm	5.1 mm	4.0-6.0 mm	2.70 mm	2000 N	2500 N	5.0 x 10 mm	5141 550 10	500
5.0 mm	12 mm	9.5 mm	1.1 mm	5.1 mm	6.0-8.0 mm	2.70 mm	2000 N	2500 N	5.0 x 12 mm	5141 550 12	500
5.0 mm	14.0 mm	9.5 mm	1.1 mm	5.1 mm	8.0-10.0 mm	2.70 mm	2000 N	2500 N	5.0 x 14.0 mm	5141 550 14	500
5.0 mm	16.0 mm	9.5 mm	1.1 mm	5.1 mm	10.0-12.0 mm	2.70 mm	2000 N	2500 N	5.0 x 16.0 mm	5141 550 16	500
5.0 mm	18.0 mm	9.5 mm	1.1 mm	5.1 mm	12.0-14.0 mm	2.70 mm	2000 N	2500 N	5.0 x 18.0 mm	5141 550 18	250
5.0 mm	21.0 mm	9.5 mm	1.1 mm	5.1 mm	14.0-17.0 mm	2.70 mm	2000 N	2500 N	5.0 x 21.0 mm	5141 550 21	250
5.0 mm	25.0 mm	9.5 mm	1.1 mm	5.1 mm	17.0-20.0 mm	2.70 mm	2000 N	2500 N	5.0 x 25.0 mm	5141 550 25	250
5.0 mm	27.0 mm	9.5 mm	1.1 mm	5.1 mm	20.0-23.0 mm	2.70 mm	2000 N	2500 N	5.0 x 27.0 mm	5141 550 27	250
5.0 mm	30.0 mm	9.5 mm	1.1 mm	5.1 mm	23.0-25.0 mm	2.70 mm	2000 N	2500 N	5.0 x 30.0 mm	5141 550 30	100
5.0 mm	35.0 mm	9.5 mm	1.1 mm	5.1 mm	25.0-30.0 mm	2.70 mm	2000 N	2500 N	5.0 x 35.0 mm	5141 550 35	100
5.0 mm	40.0 mm	9.5 mm	1.1 mm	5.1 mm	30.0-35.0 mm	2.70 mm	2000 N	2500 N	5.0 x 40.0 mm	5141 550 40	100
6.0 mm	8.0 mm	12.0 mm	1.5 mm	6.1 mm	2.0-3.0 mm	3.60 mm	3000 N	3900 N	6.0 x 8.0 mm	5141 560 8	250
6.0 mm	10.0 mm	12.0 mm	1.5 mm	6.1 mm	3.0-5.0 mm	3.60 mm	3000 N	3900 N	6.0 x 10.0 mm	5141 560 10	250
6.0 mm	12.0 mm	12.0 mm	1.5 mm	6.1 mm	5.0-7.0 mm	3.60 mm	3000 N	3900 N	6.0 x 12.0 mm	5141 560 12	250
6.0 mm	14.0 mm	12.0 mm	1.5 mm	6.1 mm	7.0-9.0 mm	3.60 mm	3000 N	3900 N	6.0 x 14.0 mm	5141 560 14	250
6.0 mm	16.0 mm	12.0 mm	1.5 mm	6.1 mm	9.0-11.0 mm	3.60 mm	3000 N	3900 N	6.0 x 16.0 mm	5141 560 16	250
6.0 mm	18.0 mm	12.0 mm	1.5 mm	6.1 mm	11.0-13.0 mm	3.60 mm	3000 N	3900 N	6.0 x 18.0 mm	5141 560 18	250
6.0 mm	22.0 mm	12.0 mm	1.5 mm	6.1 mm	13.0-17.0 mm	3.60 mm	3000 N	3900 N	6.0 x 22.0 mm	5141 560 22	250
6.0 mm	26.0 mm	12.0 mm	1.5 mm	6.1 mm	17.0-20.0 mm	3.60 mm	3000 N	3900 N	6.0 x 26.0 mm	5141 560 26	250
6.0 mm	30 mm	12 mm	1.5 mm	6.1 mm	20-24 mm	3.6 mm	3000 N	3900 N	6.0 x 30 mm	5141 560 30	250
6.4 mm	10.0 mm	13.0 mm	1.8 mm	6.5 mm	2.0-5.0 mm	3.85 mm	3120 N	4090 N	6.4 x 10.0 mm	5141 564 10	250
6.4 mm	12.0 mm	13.0 mm	1.8 mm	6.5 mm	3.0-6.0 mm	3.85 mm	3120 N	4090 N	6.4 x 12.0 mm	5141 564 12	250
6.4 mm	15.0 mm	13.0 mm	1.8 mm	6.5 mm	6.0-9.0 mm	3.85 mm	3120 N	4090 N	6.4 x 15.0 mm	5141 564 15	250
6.4 mm	18.0 mm	13.0 mm	1.8 mm	6.5 mm	9.0-13.0 mm	3.85 mm	3120 N	4090 N	6.4 x 18.0 mm	5141 564 18	250
6.4 mm	22.0 mm	13.0 mm	1.8 mm	6.5 mm	13.0-16.0 mm	3.85 mm	3120 N	4090 N	6.4 x 22.0 mm	5141 564 22	250
6.4 mm	26.0 mm	13.0 mm	1.8 mm	6.5 mm	16.0-20.0 mm	3.85 mm	3120 N	4090 N	6.4 x 26.0 mm	5141 564 26	250
6.4 mm	30.0 mm	13.0 mm	1.8 mm	6.5 mm	18.0-23.0 mm	3.85 mm	3120 N	4090 N	6.4 x 30.0 mm	5141 564 30	250