



Masking Tape

Paper masking tape for general masking applications.

▶ Heat-resistant to +80°C.

Your advantage:

The tape is also very well suited for painting work requiring baking.

▶ Very good adhesion on smooth and painted surfaces.

Your advantage:

Very good adhesion on all smooth surfaces in construction or automotive applications, e.g. painted metal, glass, chrome-plated parts or rubber. The tape can be removed immediately after painting without leaving any residue.

▶ Moisture and solvent resistant.

Your advantages:

- The tape is suitable for all painting work with all commonly available solvent-containing and water based paint and enamel systems.
- Also very well suited for wet sanding.

Width mm	Length m	Thickn. mm	Art. No.	Pack Qty.
15	50	0.13	0992 001 5	20
19			0992 001 9	16
25			0992 002 5	12
30			0992 003 0	10
38			0992 003 8	8
50			0992 005 0	6

Areas of application

- Painting and enameling of automobiles requiring baking.
- Masking for house painting jobs, attachment of masking paper.
- Marking of cartons and cans.

Specifications

Adhesive base	Natural rubber
Carrier	paper, crème-white
Adhesive strength	7.5 N / 25 mm
Elongation at rupture	10%
Application temperature	+5°C to +40°C
Temperature stability	-5°C to +80°C
Shelf life (at approx. +20°C and 50% humidity)	12 months
UV resistant	No
Moisture resistant	Yes

Instructions for use

- To assure residue-free removal, the tape must be removed immediately after drying of the paint or enamel.
- The masking tape is **not** UV-resistant and therefore not suitable for outdoor applications.

Related products

- **Border masking tape**
Art. No. **0992 66**
- **Parallel dispenser***
Art. No. **0985 053**

* for Art. No. 0992 001 9 only

These notes are intended to provide our advice to the best of our knowledge, based on tests and experience. However, we cannot assume any liability for processing results in individual cases due to the wide variety of applications as well as storage and processing conditions beyond our control. This also applies in case our technical and com-

mercial customer service is consulted free of charge and without obligation. We recommend carrying out individual tests. We guarantee the constant quality of our products. We reserve the right to make technical modifications and advanced developments.