



Washers

complying with DIN 125

Brass
Steel
A2, A4 rust proof
Polyamide PA 6.6*

* Resistant to mineral oils, petrol and weak bases.
 Temperature-resistant from -40 °C to +150 °C.



Assortments

Art. No. 0964 407
 DIN 125, **galvanised, blue passivated**
 Contents: 10 sizes from 3.2–21 mm
 = 1,425 pieces
 Sheet metal box with 12-compartment plastic insert

Art. No. 0964 407 1
 DIN 125, **galvanised, blue passivated**
 Contents: 8 sizes
 from 4.3–17 mm = 725 pieces
 4 sizes from 5.3x20 – 10.5x30 mm
 = 400 pieces
 Sheet metal box with 12-compartment plastic insert

Art. No. 0964 407 441
 DIN 125, **galvanised, yellow passivated**
 Contents: 8 sizes from 4.3–15.0 mm
 = 700 pieces
 DIN 127, spring washers, yellow passivated
 8 sizes from 4.1–14.2 mm
 = 700 pieces
 Sheet metal box with 16-compartment plastic insert

Art. No. 0964 421 00
 DIN 125, **polyamide**
 Contents: 8 sizes from 3.2–13.0 mm
 = 1,100 pieces
 Sheet metal box with 8-compartment plastic insert

Material					Brass bare	Steel bare	Steel galv., blue pass.	Steel galv., yellow pass.	A2 <small>rust proof</small>	A4 <small>rust proof</small>	Polyamide (natural)
Art. No.	→				0400	0405	0407	0407 0	0409	0412	0421 00
↓	for screws	hole Ø d mm	d ₁ mm	Thickn. h mm							
2	M 2	2.2	5	0.3	•		•				•
25	M 2.5	2.7	6	0.5			•				•
3	M 3	3.2	7	0.5	•	•	•	•	•		•
37	M 3.5	3.7	8	0.5	•		•				
4	M 4	4.3	9	0.8	•	•	•	•	•	•	•
5	M 5	5.3	10	1.0	•	•	•	•	•	•	•
6	M 6	6.4	12	1.6	•	•	•	•	•	•	•
7	M 7	7.4	14	1.6	•	•	•	•	•		•
8	M 8	8.4	16	1.6	•	•	•	•	•	•	•
10	M 10	10.5	20	2.0	•	•	•	•	•	•	•
12	M 12	13.0	24	2.5	•	•	•	•	•	•	•
14	M 14	15.0	28	2.5	•	•	•	•	•	•	
16	M 16	17.0	30	3.0	•	•	•	•	•	•	•
18	M 18	19.0	34	3.0	•	•	•	•	•		•
20	M 20	21.0	37	3.0	•	•	•	•	•	•	•
22	M 22	23.0	39	3.0		•	•	•	•	•	
24	M 24	25.0	44	4.0		•	•	•	•	•	•
26	M 26	27.0	50	4.0		•					
27	M 27	28.0	50	4.0		•					
28	M 28	29.0	50	4.0		•	•				
30	M 30	31.0	56	4.0		•	•				
32	M 32	33.0	60	5.0		•	•				
36	M 36	37.0	66	5.0		•					
38	M 38	39.0	72	6.0		•					
40	M 40	41.0	72	6.0		•					
42	M 42	43.0	78	7.0		•					
45	M 45	46.0	85	7.0		•					
48	M 48	50.0	92	8.0		•					
52	M 52	54.0	98	8.0		•					
55	M 55	57.0	105	9.0							
56	M 56	58.0	105	9.0		•					
60	M 60	62.0	110	9.0		•					
64	M 64	66.0	115	9.0							