



# Plate Springs

## DIN 2093

Steel with modulus of elasticity  $E = 206,000 \text{ N/mm}^2$

D mm	D <sub>1</sub> mm	t mm	l <sub>0</sub> mm	Steel, bare Art. No.	Pack Qty.
8	4.2	0.2	0.45	<b>0436 8 2</b>	200
		0.3	0.55	<b>0436 8 3</b>	
		0.4	0.6	<b>0436 8 4</b>	
10	5.2	0.25	0.55	<b>0436 10 025</b>	200
		0.4	0.7	<b>0436 10 4</b>	
		0.5	0.75	<b>0436 10 5</b>	
12.5	6.2	0.35	0.8	<b>0436 125 035</b>	200
		0.5	0.85	<b>0436 125 5</b>	
		0.7	1.0	<b>0436 125 7</b>	
14	7.2	0.35	0.8	<b>0436 14 035</b>	200
		0.5	0.9	<b>0436 14 5</b>	
		0.8	1.1	<b>0436 14 8</b>	
16	8.2	0.4	0.9	<b>0436 16 4</b>	200
		0.6	1.05	<b>0436 16 6</b>	
		0.9	1.25	<b>0436 16 9</b>	
18	9.2	0.45	1.05	<b>0436 18 045</b>	200
		0.7	1.2	<b>0436 18 7</b>	
		1.0	1.4	<b>0436 18 100</b>	
20	10.2	0.5	1.15	<b>0436 20 5</b>	200
		0.8	1.35	<b>0436 20 8</b>	
		1.1	1.55	<b>0436 20 110</b>	
22.5	11.5	0.6	1.4	<b>0436 225 6</b>	200
		0.8	1.45	<b>0436 225 8</b>	
		1.25	1.75	<b>0436 225 125</b>	
25	12.2	0.7	1.6	<b>0436 25 7</b>	200
		0.9	1.6	<b>0436 25 9</b>	
		1.5	2.05	<b>0436 25 150</b>	
28	14.2	0.8	1.8	<b>0436 28 8</b>	200
		1.0	1.8	<b>0436 28 100</b>	
		1.5	2.15	<b>0436 28 150</b>	
31.5	16.3	0.8	1.85	<b>0436 315 8</b>	100
		1.25	2.15	<b>0436 315 125</b>	200
		1.75	2.45	<b>0436 315 175</b>	100
35.5	18.3	0.9	2.05	<b>0436 355 9</b>	100
		1.25	2.25	<b>0436 355 125</b>	
		2.0	2.8	<b>0436 355 200</b>	
40	20.4	1.0	2.3	<b>0436 40 100</b>	100
		1.5	2.65	<b>0436 40 150</b>	
		2.25	3.15	<b>0436 40 225</b>	
45	22.4	1.25	2.85	<b>0436 45 125</b>	100
		1.75	3.05	<b>0436 45 175</b>	
		2.5	3.5	<b>0436 45 250</b>	
50	25.4	1.25	2.85	<b>0436 50 125</b>	100
		2.0	3.4	<b>0436 50 200</b>	
		3.0	4.1	<b>0436 50 300</b>	