

ROHRKABELSCHUH

Handelsüblich (DIN-ähnlich)

Drahtquerschnitt	Flanschloch	Drahtdurchmesser (d1)	Lochdurchmesser (d2)	Abstand Hülsenende - Mitte Loch (e)	Hülsenlänge (a)	Breite (b)	Art.-Nr.	VE
70 mm ²	M8	12 mm	8,4 mm	43 mm	21 mm	23 mm	0967 270 8	25
70 mm ²	M10	12 mm	10,5 mm	45 mm	21 mm	23 mm	0967 270 10	25
70 mm ²	M12	12 mm	13,2 mm	46 mm	21 mm	23 mm	0967 270 12	25
70 mm ²	M16	12 mm	17 mm	49 mm	21 mm	28 mm	0967 270 16	25
95 mm ²	M8	13,5 mm	8,4 mm	48 mm	25 mm	26 mm	0967 295 8	25
95 mm ²	M10	13,5 mm	10,5 mm	48 mm	25 mm	26 mm	0967 295 10	25
95 mm ²	M12	13,5 mm	13,2 mm	49 mm	25 mm	26 mm	0967 295 12	25
95 mm ²	M16	13,5 mm	17 mm	52 mm	25 mm	28 mm	0967 295 16	25
95 mm ²	M20	13,5 mm	21 mm	58 mm	25 mm	36 mm	0967 295 20	25
120 mm ²	M8	15 mm	8,4 mm	51 mm	26 mm	28 mm	0967 212 08	25
120 mm ²	M10	15 mm	10,5 mm	51 mm	26 mm	28 mm	0967 212 010	25
120 mm ²	M12	15 mm	13,2 mm	51 mm	26 mm	28 mm	0967 212 012	25
120 mm ²	M16	15 mm	17 mm	53 mm	26 mm	30 mm	0967 212 016	25
120 mm ²	M20	15 mm	21 mm	59 mm	26 mm	36 mm	0967 212 020	25
150 mm ²	M10	16,5 mm	10,5 mm	58 mm	30 mm	31 mm	0967 215 010	25
150 mm ²	M12	16,5 mm	13,2 mm	58 mm	30 mm	31 mm	0967 215 012	25
150 mm ²	M16	16,5 mm	17 mm	58 mm	30 mm	31 mm	0967 215 016	25
150 mm ²	M20	16,5 mm	21 mm	64 mm	30 mm	36 mm	0967 215 020	25
185 mm ²	M10	19,4 mm	10,5 mm	65 mm	30 mm	36 mm	0967 218 510	25
185 mm ²	M12	19,4 mm	13,2 mm	65 mm	30 mm	36 mm	0967 218 512	25
185 mm ²	M16	19,4 mm	17 mm	65 mm	30 mm	36 mm	0967 218 516	25
185 mm ²	M20	19,4 mm	21 mm	69 mm	30 mm	39 mm	0967 218 520	25
240 mm ²	M10	21,2 mm	10,5 mm	72 mm	35 mm	39 mm	0967 224 010	25
240 mm ²	M12	21,2 mm	13,2 mm	72 mm	35 mm	39 mm	0967 224 012	25
240 mm ²	M16	21,2 mm	17 mm	72 mm	35 mm	39 mm	0967 224 016	25
240 mm ²	M20	21,2 mm	21 mm	72 mm	35 mm	39 mm	0967 224 020	25

ORSY-lagerfähig