



Տափօղակներ

DIN 2093

Պողպատ, առաձգականության մոդուլը
E = 206,000 Ն/մմ²

D մմ	D ₁ մմ	t մմ	l ₀ մմ	Ողորկ պողպատ Արտիկուլ	Փ./հատ
8	4.2	0.2	0.45	0436 8 2	200
		0.3	0.55	0436 8 3	
		0.4	0.6	0436 8 4	
10	5.2	0.25	0.55	0436 10 025	200
		0.4	0.7	0436 10 4	
		0.5	0.75	0436 10 5	
12.5	6.2	0.35	0.8	0436 125 035	200
		0.5	0.85	0436 125 5	
		0.7	1.0	0436 125 7	
14	7.2	0.35	0.8	0436 14 035	200
		0.5	0.9	0436 14 5	
		0.8	1.1	0436 14 8	
16	8.2	0.4	0.9	0436 16 4	200
		0.6	1.05	0436 16 6	
		0.9	1.25	0436 16 9	
18	9.2	0.45	1.05	0436 18 045	200
		0.7	1.2	0436 18 7	
		1.0	1.4	0436 18 100	
20	10.2	0.5	1.15	0436 20 5	200
		0.8	1.35	0436 20 8	
		1.1	1.55	0436 20 110	
22.5	11.5	0.6	1.4	0436 225 6	200
		0.8	1.45	0436 225 8	
		1.25	1.75	0436 225 125	
25	12.2	0.7	1.6	0436 25 7	200
		0.9	1.6	0436 25 9	
		1.5	2.05	0436 25 150	
28	14.2	0.8	1.8	0436 28 8	200
		1.0	1.8	0436 28 100	
		1.5	2.15	0436 28 150	
31.5	16.3	0.8	1.85	0436 315 8	100
		1.25	2.15	0436 315 125	200
		1.75	2.45	0436 315 175	100
35.5	18.3	0.9	2.05	0436 355 9	100
		1.25	2.25	0436 355 125	
		2.0	2.8	0436 355 200	
40	20.4	1.0	2.3	0436 40 100	100
		1.5	2.65	0436 40 150	
		2.25	3.15	0436 40 225	
45	22.4	1.25	2.85	0436 45 125	100
		1.75	3.05	0436 45 175	
		2.5	3.5	0436 45 250	
50	25.4	1.25	2.85	0436 50 125	100
		2.0	3.4	0436 50 200	
		3.0	4.1	0436 50 300	