



PTFE Thread Sealing Tape

Application

Used to seal thread connections.

Designation	Width in mm	Length in m	Thickn. in mm	Surface-based mass g/m ²	DVGW- tested	For	Art. No.	P. Qty.
FRp PTFE Thread Sealing Tape	12	12	0.1	60	x	Fine thread (DN ≤ 10)	0985 030 160	10
GRp PTFE Thread Sealing Tape	12	12	0.1	100	x	Coarse thread (10 < DN ≤ 50)	0985 030 161	
PTFE Thread Sealing Tape	12	12	0.08	25	–	–	0985 030 165	

Advantages

- DVGW-tested (thickness: 0.1 mm) pursuant to DIN EN 751/3 (97) and DIN 30660 (99).
- Resistant to all aggressive media.
- Thermal stability* –240°C to +240°C.
- Pressure resistance* up to 25 bar.
- Does not stick or swell.
- Therefore prevents seizing of the thread.
- Alignment of the thread connection, which includes limited turn-back, is permissible.

* Since the temperature and pressure are dependent on one another, it is not permissible to allow both to be pushed to maximum levels simultaneously. In addition, the specifications depend on the respective medium. For this reason, these specifications can only serve as a guideline due to the variety of application options (see also DVGW approval).