

Engine oil TRIATHLON® Universal SAE 15W-40

High-performance, multigrade engine oil for optimum lubrication and a long engine service life

Good wear protection properties and prevention of black sludge formation

Low oil consumption and very resistant to ageing, viscosity and temperatures

Mineral oil

TRIATHLON engine oils are produced and packaged in compliance with the most stringent quality specifications in line with DIN EN ISO 9001

- High product safety
- Extensive manufacturer approvals

Only high-quality first raffinates and raw materials are used in TRIATHLON oils

Satisfies important specifications of automotive manufactures



Illustration only

Type of oil	Mineral
Viscosity grade	15W-40
Approved for engine oils	API SL, API CF, API CG 4, MB 228.3, MB 229.1, Caterpillar TO-2, ACEA A3/B4, ACEA E2 #5, Allison C4
Recommended applications for engine oils	Mack EO-L, MTU Type 2, Volvo VDS, MAN M3275-1, PSA B71 2295
Shelf life from production	60 Month

Contents	Art. no.	P. Qty.
1 l	0897 115 401	1/12
5 l	0897 115 402	1/3
20 l	0897 115 403	1
60 l	0897 115 404	1
208 l	0897 115 405	1

Details/Application

Year-round engine oil for petrol and diesel engines with or without exhaust-gas turbocharging (EGT)

Proof of performance

ACEA A3-04/B4-04/E2-96 #5, API SL/CF/CG-4, Allison C4, Caterpillar TO-2

Würth also recommends this product for vehicles that comply with the following specifications:

Volvo VDS, Mack EO-L, MTU type-2, MB release 229.1, MB release 228.3

Notice

Observe the operating instructions of the vehicle and engine manufacturer for standard and extended oil change intervals.

The usage instructions are recommendations based on the tests we have conducted and based on our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.

Related products	Art. no.
Hand-lever drum pump	0891 621
Compressed air drum pump	0891 625
Catch tray	0962 897