

Engine oil TRIATHLON® Extra 5W-30

Low-viscosity, smooth-running oil for year-round use

High level of wear protection and reduced friction for extended engine service life

HC synthetic oil

TRIATHLON engine oils are produced and packaged in compliance with the most stringent quality specifications in line with DIN EN ISO 9001

- High product safety
- Extensive manufacturer approvals

Only high-quality first raffinates and raw materials are used in TRIATHLON oils

Satisfies important specifications of automotive manufactures



Illustration only

Type of oil	HC synthesis
Viscosity grade	5W-30
Approved for engine oils	ACEA A1-02, ACEA A5-02, ACEA B1-02, API SL, Ford WSS-M2C 913-A, Ford WSS-M2C 913-B, Ford WSS-M2C 912-A1, ILSAC GF-2
Shelf life from production	60 Month

Contents	Art. no.	P. Qty.
5 l	0897 905 302	1/3
20 l	0897 905 303	1
60 l	0897 905 304	1
208 l	0897 905 305	1

Details/Application

Low-viscosity smooth-running oil for year-round use. For passenger cars.

Proof of performance

ACEA A1-02/A5-02/B1-02, API SL, Ford WSS-M2C 913-A/WSS-M2C 913-B/WSS-M2C 912-A1, ILSAC GF-2

Tested for turbochargers and catalytic converters

Notice

Observe the operating instructions of the vehicle and engine manufacturer for standard and extended oil change intervals.

The usage instructions are recommendations based on the tests we have conducted and based on our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.

Related products for	Designation	Art. no.
0897 905 304	Hand-lever drum pump	0891 621
	Compressed air drum pump	0891 625
	Catch tray	0962 897
0897 905 305	Hand-lever drum pump	0891 621
	Compressed air drum pump	0891 625
	Catch tray	0962 897