

Engine oil TRIATHLON® Diesel 15W-40

Multigrade engine oil for year-round use

High resistance to shearing

Prevents black sludge from forming

Optimum lubrication

TRIATHLON engine oils are produced and packaged in compliance with the most stringent quality specifications in accordance with DIN EN ISO 9001

- High product safety
- Extensive manufacturer approvals

Only high-quality first raffinates and raw materials are used in TRIATHLON oils

Satisfies important specifications of automotive manufacturers



Type of oil	Mineral
Viscosity grade	15W-40
Recommended applications for engine oils	Volvo VDS, Allison C4, Caterpillar TO-2, MIL-L 2104 E, MIL-L 46152 D, MTU Type 1, MAN 271
Shelf life from production	60 Month

Contents	Approved for engine oils	Art. no.	P. Qty.
20 l	ACEA A2-96, ACEA B3-98, ACEA E2-96 #5, API SJ, API CF 4, API CF, MB 228.1	0897 215 403	1
60 l	ACEA B3-98, ACEA E2-96 #5, API SJ, API CF 4, API CF, MB 228.1	0897 215 404	1
208 l	ACEA B3-98, ACEA E2-96 #5, API SJ, API CF 4, API CF, MB 228.1	0897 215 405	1

Details/Application

For lorries, multigrade engine oil for year-round use. High shearing stability, prevents black sludge formation.

Notice

Observe the operating instructions of the vehicle and engine manufacturer for standard and extended oil change intervals.

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.