

TECHNICAL DATA SHEET

Gearbox oil TRIATHLON® Automatic Ultra

Art. no. 0897 420 003

P. Qty.: 1

High-performance gearbox oil for automatic gearboxes

- Very good low-temperature properties
- Optimal viscosity/temperature properties
- Excellent wear and favourable friction behaviour
- Excellent corrosion protection
- Ages well
- Broad range of uses



Contents	20 l
Type of oil	HC synthesis
Approved for gear oils	GM Dexron IIIH, JASO 1-A, Toyota Type T-II, Toyota Type T-IV, Allison C4, TES 295, Kia SP II, Kia SP III, Mitsubishi SP II, Mitsubishi SP III, Hyundai SP II, Hyundai SP III, Mazda ATF M III, Mazda ATF M V, Honda ATF Z1 (except CVTs), Ford Mercon V, Nissan AT-Matic J Fluid, Nissan AT-Matic D Fluid, Nissan AT-Matic K Fluid
Recommended applications for gear oils	JWS 3309, Chrysler ATF +3, Chrysler ATF +4, MB 236.2, MB 236.5, MB 236.6, MB 236.7, MB 236.9, MB 236.10, Daimler NAG-1, BMW LT 71 141, BMW LA 2634, BMW 7045 E, BMW 8072 B, MAN 339 Type Z2, MAN 339 Type V1, ZF-TE-ML 02F, ZF-TE-ML 03D, ZF-TE-ML 04D, ZF-TE-ML 05L, ZF-TE-ML 09, ZF-TE-ML 11A, ZF-TE-ML 11B, ZF-TE-ML 14B, ZF-TE-ML 17C, VW G 052 162, VW G 055 025, Volvo 97340, Volvo 97341, Subaru ATF, Voith H55.6335.xx, Allison TES 295
Shelf life from production	60 Month
Density	0.85 g/cm ³
Density conditions	at 15 °C
Min. flashing point	210 °C

TECHNICAL DATA SHEET

Pour point	-50 °C
------------	--------

Application area

High-performance gearbox oil for automatic transmissions.

Application information

Ideally suited for automatic gearboxes, manual gearboxes, steering systems, hydraulic systems and auxiliary drives, not only in passenger cars and commercial vehicles, but also in industrial applications.

Meets all the important specifications from vehicle manufacturers (see Würth Online Shop).

Notice

Observe the operating instructions of the vehicle and engine manufacturer for standard and extended oil change intervals.

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications as well as storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by the provision of this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee the consistent quality of our products. We reserve the right to make technical changes and further develop products.