


ALG 18 V M-CUBE charger



Suitable for Li-Ion 18 V BASIC M-CUBE rechargeable batteries

- For charging the Li-ion 18 V M-CUBE BASIC rechargeable battery

3-year Würth power tool guarantee on wear and tear damages and replacement of batteries and chargers.

The guarantee is subject to the current terms and conditions, which must be followed.

3 Years Warranty on manufacturing and material defects

Excluded are damages caused by improper use, overloading or failure to observe the operating instructions.

Input voltage	230 V/AC
Min./max. output voltage	18-18 V/DC
Suitable batteries	M-CUBE 18V
Min./max. frequency	50/60 Hz
Cable length	1.5 m
Length	195 mm
Width	130 mm
Height	80 mm
Max. output voltage	18 V/DC
Max. frequency	60 Hz
Min. frequency	50 Hz
Max. input voltage	240 V/AC
Min./max. input voltage	220-240 V/AC
Min. temperature conditions	0 °C
Service component	Charger for machine
Min. output voltage	18 V/DC
Plug type	F
WEEE (taking back waste electrical and electronic equipment)	5
Nominal voltage	18 V/DC
Output voltage	18 V/DC

Art. no.	5705 180 000	5705 860 000
P. Qty.	1	1
Type description	ALG 18/4 BASIC	ALG 18/6 FAST
Max. charging current	4 A	6 A
Power output		165 W
Charging time	45 min	30 min
Min./max. temperature conditions		0 to 40 °C
Max. temperature conditions		40 °C
Product weight (per item)	760 g	1015 g