

## 2C liquid metal filler FLM 50

**Fast-acting repair system for installers and workshops in the metalworking sector. Particularly suitable for filling moulds, and for sealing and covering leaking areas.**

### 2-component reaction resin system with special formula

Similar characteristics to metal make it ideal for use in the metalworking sector.

### Quick to harden

Ideal for minor repairs requiring quick turnaround.

### Very high final strength

Easy further processing such as turning, milling, drilling, filing and thread cutting once hardened.

### Handy dual cartridge

Guarantees optimum mixing ratio.



Contents	50 ml
Chemical basis	Epoxy
Colour	Grey
Min. functional strength	30 min
Min. final strength	24 h
Min./max. processing temperature	20 to 25 °C
Min./max. temperature resistance of the hardened material	-45 to 120 °C
Shelf life from production	24 Month
Min./max. curing time	10-12 min

### Art. no. 0893 680

P. Qty.: 1 / 10

### Details/Application

Repair compound for covering, bonding, filling and levelling on a variety of materials.

Fast repair system for fitters and workshops in the metalworking sector. Particularly suitable for filling moulds, and for sealing and covering leaks.



## Instructions

The application surfaces must be clean, dry and free of grease. The static mixing tube is connected to the opened adhesive cartridge and the cartridge is inserted into the respective dosing gun.

Discard the first 5-10 cm of mixed adhesive.

Apply the mixed adhesive to the parts to be adhered as quickly as possible.

For more information, please refer to the technical data sheet.

## Notice

The metals must be cleaned and degreased bare. The hardened liquid metal can be easily machined by lathing, milling, drilling etc.

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.

Related products for	Designation	Art. no.
0893 680	Static mixing tube for 2C adhesives	<b>0891 481</b>
	Plastic double cartridge gun for 38 ml and 50 ml double cartridges	<b>0891 893 486</b>
	Metal cleaner 500 ml	<b>0890 107 063</b>
	Universal cleaner type 60 1 l	<b>0892 130 030</b>
	Tex-Rein cleaning cloth 150 PCS	<b>0899 810</b>