


Lock washer For shafts, DIN 6799, stainless steel 1.4122

DIN	6799
Material	Stainless steel, 1.4122
Surface	Plain
RoHS-compliant	Yes



Suitable for groove diameter	Suitable for min./max. shafts	Internal diameter (d ₁)	Outer diameter (d ₂)	Thickness (s ₁)	Art. no.	P. Qty.
1.2 mm	1.4-2 mm	1.01 mm	3.25 mm	0.3 mm	0431 011 20	5000
1.5 mm	2-2.5 mm	1.28 mm	4.25 mm	0.4 mm	0431 011 5	1000
1.9 mm	2.5-3 mm	1.61 mm	4.8 mm	0.5 mm	0431 011 9	1000
2.3 mm	3-4 mm	1.94 mm	6.3 mm	0.6 mm	0431 012 3	500/1000
3.2 mm	4-5 mm	2.7 mm	7.3 mm	0.6 mm	0431 013 2	500/2500
4 mm	5-7 mm	4 mm	9.3 mm	0.7 mm	0431 014	500/1000
5 mm	6-8 mm	4.11 mm	11.3 mm	0.7 mm	0431 015	500/1000
6 mm	7-9 mm	5.26 mm	12.3 mm	0.7 mm	0431 016	500/2500
7 mm	8-11 mm	5.84 mm	14.3 mm	0.9 mm	0431 017	200/1000
8 mm	9-12 mm	6.52 mm	16.3 mm	1 mm	0431 018	200/500
9 mm	10-14 mm	7.63 mm	18.8 mm	1.1 mm	0431 019	1000
10 mm	11-15 mm	8.32 mm	20.4 mm	1.2 mm	0431 011 0	100/1000
12 mm	13-18 mm	10.45 mm	23.4 mm	1.3 mm	0431 011 2	100/1000
15 mm	16-24 mm	12.61 mm	29.4 mm	1.5 mm	0431 011 50	100
19 mm	20-31 mm	15.92 mm	37.6 mm	1.75 mm	0431 011 90	100
24 mm	25-38 mm	21.88 mm	44.6 mm	2 mm	0431 012 4	50