


SL locking device

Phosphated steel

- Shaft retainer that can be installed and removed radially without tools.
- Spring-loaded arms for compensation of length tolerances.
- Axial pretensioning for rattle-free fit.
- Double locking to prevent accidental stripping.
- High axial load capacity.



Material	Steel
Surface	Phosphated
RoHS-compliant	Yes
Form	ESN08



Suitable for shafts (d_2)	Suitable for groove diameter (d_3)	Suitable for groove width (m_1)	Internal diameter (d_1)	Width (b_1)	Height (h_1)	Art. no.	P. Qty.
4 mm	3.2 mm	0.65 mm	3.4 mm	7 mm	9 mm	0491 4	50/1000
5 mm	4 mm	0.75 mm	4.2 mm	9 mm	11 mm	0491 5	50/1000
6 mm	5 mm	0.75 mm	5.2 mm	11 mm	14 mm	0491 6	50/1500
8 mm	6 mm	0.95 mm	6.2 mm	14 mm	17.5 mm	0491 8	50/500
10 mm	8 mm	1.05 mm	8.2 mm	18 mm	22 mm	0491 10	25/900
12 mm	9 mm	1.15 mm	9.4 mm	22 mm	26 mm	0491 12	25/500
16 mm	12 mm	1.35 mm	12.4 mm	28 mm	34 mm	0491 16	25/100

Can be stored in the ORSY system