

Blow gun with soft handle



Extremely versatile and reliable blow gun with non-slip handle for a wide range of applications

- Continuously adjustable
- Insulated and ergonomic 2C soft handle
- Light but robust design
- Suitable for compressed air and non-explosive liquids

Air consumption	500 l/min
Min./max. temperature conditions	-20 to 60 °C
Sound-pressure level	94 dB
Pneumatic connection	1/4 inch FT
Max. operating pressure	16 bar
Material	Polyoxymethylene

Design	Pipe length	Weight	Nozzle hole diameter	Art. no.	P. Qty.
Tube angled	90 mm	130 g	3.5 mm	0714 923 1	1
Tube straight	320 mm	140 g	2.9 mm	0714 923 3	1
Tube straight	490 mm	150 g	2.9 mm	0714 923 4	1

Related products for	Designation	Art. no.
0714 923 1	Plug-in nipple series 2000 14 mm 39 mm R 1/4 inch ET	0699 100 614
	Rubber nozzle for blow guns 14 mm	0714 92 24
	More effective with bypass 14 mm	0714 92 25
0714 923 3	Plug-in nipple series 2000 14 mm 39 mm R 1/4 inch ET	0699 100 614
	Rubber nozzle for blow guns 14 mm	0714 92 24
	More effective with bypass 14 mm	0714 92 25
0714 923 4	Plug-in nipple series 2000 14 mm 39 mm R 1/4 inch ET	0699 100 614
	Rubber nozzle for blow guns 14 mm	0714 92 24
	More effective with bypass 14 mm	0714 92 25